

2CLG(30~300)KV 50mA

电流范围 ● 50mA ● 100mA ● 200mA ● 300mA ● 500mA ● 1A ● 1.5A ● 2A ● 2.5A ● 3A ● 5A

产品特点

1. 采用最先进的工艺水平制作的管芯组合
2. 低漏电流、低功率、工作结温 $-40^{\circ}\text{C} \sim +175^{\circ}\text{C}$
3. 优异的瞬间大电流抗冲击性能及反向雪崩击穿特性
4. 独创散热设计、高效的热传导性能
5. 低功耗、低漏流。



型号	反向重复峰值电压 V_{RRM}	正向平均整流电流 $I_{F(AV)}$	最大正向峰值电压 V_{FM}	最大正向浪涌电流 I_{FSM}	常温反向直流电流 I_{RRM}	最大反向恢复时间 t_{rr}	外形尺寸 $L \times H \times B$	PDF下载
Type	KV	A	V	A	μA	nS	mm	
2CLG30KV/0.05A	30	0.05	54	1	2	100	80 × 10 × 10 图示	PDF
2CLG50KV/0.05A	50	0.05	90	1	2	100	80 × 18 × 10 图示	PDF
2CLG60KV/0.05A	60	0.05	108	1	2	100	120 × 25 × 18 图示	PDF
2CLG80KV/0.05A	80	0.05	144	1	2	100	130 × 27 × 17 图示	PDF
2CLG100KV/0.05A	100	0.05	180	1	2	100	150 × 27 × 17 图示	PDF
2CLG150KV/0.05A	150	0.05	270	1	2	100	150 × 27 × 17 图示	PDF
2CLG200KV/0.05A	200	0.05	360	1	2	100	200 × 27 × 17 图示	PDF
2CLG250KV/0.05A	250	0.05	450	1	2	100	245 × 27 × 17 图示	PDF
2CLG300KV/0.05A	300	0.05	540	1	2	100	245 × 27 × 17 图示	PDF

